

PRODUCT NAME: PARK AVE S/G HMIS CODES: H F R P
PRODUCT CODE: 4250, 4200, 4210, 4220, 4230, 4260 2 2 0 B

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: PARKER PAINT
ADDRESS: PO BOX 11047
3003 SOUTH TACOMA WAY
TACOMA, WA 98409
EMERGENCY PHONE: 1-800-255-3924 DATE PRINTED: 10/29/97
INFORMATION PHONE: 253-473-1122 NAME OF PREPARER: J. BURNWORTH

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	VAPOUR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
* AROMATIC HYDROCARBON	64742-95-6	66	11
* OSHA PEL: 100 PPM, ACGIH TLV: NOT ESTAB.			
* NAPHTHA, HEAVY ALKYLATE (ODORLESS)	64741-65-7	66	10
* OSHA PEL: 100 PPM, ACGIH TLV: 100 PPM			
* RULER 66 MINERAL SPIRITS	8052-41-3	66	4
* OSHA PEL: 100 PPM, ACGIH TLV: 100 PPM			
* 1,2,4 TRIMETHYLBENZENE	95-63-6		0.28
* OSHA PEL: 25 PPM, ACGIH TLV: 25 PPM			
* ETHYLBENZENE	100-41-4		0.12
* OSHA PEL: 100 PPM, ACGIH TLV: 100 PPM			

*INDICATES CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF SARA TITLE III AND OF 40 CFR 372 ARE PRESENT.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS
BOILING RANGE: 314 Deg F
SPECIFIC GRAVITY (H20-1): 1.33
VAPOR DENSITY: HEAVIER THAN AIR
EVAPORATION RATE: SLOWER THAN ETHER
SOLUBILITY IN WATER: INSOLUBLE
APPEARANCE AND ODOR: COLORED LIQUID WITH AN ALIPHATIC ODOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA
FLASH POINT: 105 Deg F
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1
EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL
SPECIAL FIREFIGHTING PROCEDURES

SECTION V - REACTIVITY DATA
FULL PROTECTIVE EQUIPMENT, INCLUDING A SELF-CONTAINED BREATHING APPARATUS, SHOULD BE USED. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD UP AND POSSIBLE AUTO-IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

UNUSUAL FIRE AND EXPLOSION HAZARDS
KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DURING EMERGENCY CONDITIONS, OVER EXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD.

SECTION VI - HEALTH HAZARD DATA
STABILITY: STABLE
CONDITIONS TO AVOID: EXTREME HEAT, SPARKS OR OPEN FLAME.

INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZING MATERIALS.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: INCOMPLETE COMBUSTION CAN PRODUCE CARBON MONOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
INHALATION OF HIGH CONCENTRATIONS OF VAPORS MAY LEAD TO NASAL IRRITATION, HEADACHE, NAUSEA, ASPHYXIATION OR UNCONSCIOUSNESS.
SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE
REPEATED CONTACT CAN CAUSE SKIN IRRITATION AND DERMATITIS. EYE CONTACT CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING OR BLURRED VISION.

SECTION VIII - CONTROL MEASURES
RESPIRATORY PROTECTION
NEAR A PROPERLY FITTED NIOSH/MSHA APPROVED VAPOR/PARTICULATE RESPIRATOR OR AN AIR-SUPPLYING RESPIRATOR UNLESS VENTILATION IS ADEQUATE TO KEEP AIRBORNE CONTAMINATION BELOW APPLICABLE OSHA, PEL OR ACGIH TLV OCCUPATIONAL EXPOSURE LIMITS.

SECTION IX - DISCLAIMER
WORK/HYGIENIC PRACTICES: WASH HANDS BEFORE EATING OR USING THE RESTROOM.
AS OF THE DATE OF PREPARATION OF THIS DOCUMENT, THE FORGOING INFORMATION IS BELIEVED TO BE ACCURATE AND IS PROVIDED IN GOOD FAITH. COMPLY WITH APPLICABLE FEDERAL AND STATE LAWS (S). HOWEVER, NO WARRANTY OR REPRESENTATION WITH RESPECT TO SUCH INFORMATION IS INTENDED OR GIVEN.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
NONE ARE KNOWN AT THIS TIME.
INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
SWALLOWING CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. VOMITING CAN RESULT IN ASPIRATION OF MATERIAL INTO THE LUNGS WHICH CAN CAUSE CHEMICAL PNEUMONITIS.

HEALTH HAZARDS (ACUTE AND CHRONIC)
ACUTE: (SHORT TERM) OVER EXPOSURE CAN CAUSE SKIN AND EYE IRRITATION. INHALATION CAN CAUSE ACUTE NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY NASAL IRRITATION, HEADACHE, DIZZINESS, CONFUSION OR UNCONSCIOUSNESS. CHRONIC: (LONG TERM) OVER EXPOSURE TO VAPORS MAY CAUSE KIDNEY OR LIVER DAMAGE.

CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO
LABORATORY STUDIES WITH RATS HAVE SHOWN THAT PETROLEUM DISTILLATES CAUSE KIDNEY AND LIVER DAMAGE OR TUMORS. SEVERAL STUDIES EVALUATING PETROLEUM WORKERS HAVE NOT SHOWN SIGNIFICANT INCREASES OF KIDNEY DAMAGE, NOR KIDNEY OR LIVER TUMORS.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN AT THIS TIME

EMERGENCY AND FIRST AID PROCEDURES
INHALATION: REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED, APPLY ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN. EYE CONTACT: WASH EYES WITH CLEAN WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN. SKIN CONTACT: WASH AFFECTED AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN IF IRRITATION PERSISTS. INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING! CONSULT A PHYSICIAN OR POISON CONTROL CENTER

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
VENTILATE THE AREA. REMOVE ALL SOURCES OF IGNITION (FLAME, HOT SURFACES, ELECTRICAL, STATIC OR FRICTIONAL SPARKS). AVOID SKIN CONTACT AND BREATHING VAPORS. CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

WASTE DISPOSAL METHOD
DO NOT ALLOW MATERIAL TO CONTAMINATE GROUND WATER SYSTEMS. ABSORB LARGER SPILLS WITH SAND, CLAY OR DIATOMACEOUS EARTH. DISPOSE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL DISPOSAL REQUIREMENTS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE IN A COOL, WELL VENTILATED AREA AWAY FROM SOURCES OF IGNITION. STORE LARGER QUANTITIES ONLY IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106.

OTHER PRECAUTIONS: DO NOT FEED INTERNALLY. KEEP OUT OF REACH OF CHILDREN.