

95A

— SECTION I —
PRODUCT IDENTIFICATION

MATERIAL SAFETY DATA SHEET



THE SHERWIN - WILLIAMS CO.
101 PROSPECT AVE. N.W.
CLEVELAND, OH 44115

EMERGENCY TELEPHONE NO.
(216) 566-2917
INFORMATION TELEPHONE NO.
(216) 566-2902

DATE OF PREPARATION
1 - Nov - 95


©1995, The Sherwin-Williams Co.

Super Acrylic™ Controls Rust Spray Enamel

140-SCR/1

— SECTION II —					12 ounces Net Weight												
CAS No.	HAZARDOUS INGREDIENT (percent by weight)	ACGIH TLV <STEL>	OSHA PEL <STEL>	Units	Vapor Pressure (mm Hg)	140-0506 Gloss Black	140-0514 Wr. Iron Flat Black	140-0522 Gloss White	140-0530 Chrome Aluminum	140-0548 Safety Red	140-0555 Federal Blue	140-0563 Gloss Brown	140-0571 Safety Yellow	140-0589 Red Metal Primer	140-0597 Wr. Iron Flat White	140-0613 Gray Metal Primer	140-0621 Machinery Gray
74-98-6	Propane (propellant)		1000	PPM	760.0	14	14	14	15	15	15	14	14	15	15	15	14
106-97-8	Butane (propellant)	800	800	PPM	760.0	13	13	13	15	14	14	13	13		14		13
108-88-3	§ Toluene	50	100 <150>	PPM (Skin)	22.0	12	10	12	58	8	18	9		8	6	5	12
100-41-4	§ Ethylbenzene	100 <125>	100 <125>	PPM	7.1	3	3	3		3	2	2	4	3	2	3	3
1330-20-7	§ Xylene	100 <150>	100 <150>	PPM	5.9	18	18	16		17	11	12	23	17	14	15	17
95-63-6	§ 1,2,4-Trimethylbenzene	25	25	PPM	2.0	1											
67-64-1	Acetone	750 <1000>	750 <1000>	PPM	180.0	22	18	16		18	18	26	28	32	21	40	21
78-93-3	§ Methyl Ethyl Ketone	200 <300>	200 <300>	PPM	70.0												
763-69-9	Ethyl 3-Ethoxypropionate.	Not Established			1.1			3			3	3	4	2		2	4
14807-96-6	Talc	2	2	Mg/M3	as Resp. Dust		9							6		5	
471-34-1	Calcium Carbonate.	10	15[5]	Mg/M3	as Dust [Resp. Fraction]		2								9		
13463-67-7	Titanium Dioxide.	10	10[5]	Mg/M3	as Dust [Resp. Fraction]			10			3		1		9	3	4
VOC as a percent by weight, per BAAQMD Rule 49						85	79	77	88	83	81	80	83	76	74	80	82
HMIS® Ratings (Health - Flammability - Reactivity)						2 4 0	2 4 0	2 4 0	2 4 1	2 4 0	2 4 0	2 4 0	2 4 0	2 4 0	2 4 0	2 4 0	2 4 0

§ Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C



→→→ MSDS Text Page Follows →→→

Super Acrylic™ Controls Rust Spray Enamel

140-SCR

Section III — PHYSICAL DATA

PRODUCT WEIGHT -- N.A.
SPECIFIC GRAVITY -- N.A.
BOILING RANGE -- <0-342 °F
SOLUBILITY IN WATER -- N.A.
EVAPORATION RATE -- Faster than Ether
VAPOR DENSITY -- Heavier than Air
MELTING POINT -- N.A.

Section IV — FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION FLASH POINT <0 °F PMCC LEL 0.7 UEL 12.8
Extremely Flammable, Flash below 21 °F
EXTINGUISHING MEDIA
Carbon Dioxide, Dry Chemical, Foam
UNUSUAL FIRE AND EXPLOSION HAZARDS
Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.
SPECIAL FIRE FIGHTING PROCEDURES
Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section V — HEALTH HAZARD DATA

ROUTES OF EXPOSURE
Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.
ACUTE Health Hazards
EFFECTS OF OVEREXPOSURE
Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.
SIGNS AND SYMPTOMS OF OVEREXPOSURE
Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.
Redness and itching or burning sensation may indicate eye or excessive skin exposure.
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
None generally recognized.
EMERGENCY AND FIRST AID PROCEDURES
If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
If on SKIN: Wash affected area thoroughly with soap and water.
Remove contaminated clothing and launder before re-use.
If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
If SWALLOWED: Seek medical attention.
CHRONIC Health Hazards
No ingredient in these products is an IARC, NTP or OSHA listed carcinogen.
Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to the liver, urinary, cardiovascular, and reproductive systems.
Rats exposed to titanium dioxide dust at 250 mg./m3 developed lung cancer, however, such exposure levels are not attainable in the workplace.
Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Section VI — REACTIVITY DATA

STABILITY — Stable
CONDITIONS TO AVOID
None known.
INCOMPATIBILITY
None known.
HAZARDOUS DECOMPOSITION PRODUCTS
By fire: Carbon Dioxide, Carbon Monoxide
HAZARDOUS POLYMERIZATION — Will Not Occur

Section VII — SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Remove all sources of ignition. Ventilate and remove with inert absorbent.
WASTE DISPOSAL METHOD
Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.
Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section VIII — PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE
Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.
These coatings may contain materials classified as nuisance particulates (listed "as Dust" in Section II) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section II, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m3 (total dust), OSHA PEL 15 mg./m3 (total dust), 5 mg./m3 (respirable fraction).
VENTILATION
Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.
RESPIRATORY PROTECTION
If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.
When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for protection against non-volatile materials in Section II.
PROTECTIVE GLOVES
None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.
EYE PROTECTION
Wear safety spectacles with unperforated sideshields.

Section IX — PRECAUTIONS

DOL STORAGE CATEGORY — 1A
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Contents are EXTREMELY FLAMMABLE. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.
During use and until all vapors are gone: Keep area ventilated — Do not smoke — Extinguish all flames, pilot lights, and heaters — Turn off stoves, electric tools and appliances, and any other sources of ignition.
Consult NFPA Code. Use approved Bonding and Grounding procedures.
Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120 °F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.
OTHER PRECAUTIONS
Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section X — OTHER REGULATORY INFORMATION

CALIFORNIA PROPOSITION 65
WARNING: These products contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.