

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION					
NFPA Rating: Health-1; Flammability-1; Reactivity-0; Special--		HMS Rating: Health-1; Flammability-1; Reactivity-0; Personal Protection-B			
Manufacturer's Name: AMREP, INC.		DOT Hazard Classification: ORM-D			
Address: 990 Industrial Park Drive Marietta, GA 30062		Identity (trade name as used on label): MISTY WATER BASED CHALKBOARD AND WHITEBOARD CLEANER			
Date Prepared: 03/10/05 Prepared By: IB/TR		MSDS Number: A00101 Revision: 16			
Information Calls: (770)422-2071		NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA			
EMERGENCY RESPONSE NUMBER: 1(800)255-3924					
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION					
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
2-BUTOXYETHANOL*	111-76-2	Yes*	25 (skin)	20 (skin)	d
ETHANOL	64-17-5	No	1000	1000	d
ISOBUTANE / PROPANE BLEND	75-28-5	No	800	800	d
	74-98-6	No	1000	1000	d
*GLYCOL ETHER					
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS					
Boiling Point: N/A		Specific Gravity (H2O=1): Concentrate Only =0.985			
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.70		Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A			
Vapor Density (Air = 1): N/E		Evaporation Rate (= 1): N/E			
Solubility in Water: Soluble		Water Reactive: No			
Appearance and Odor: White foam, sassafras fragrance.					
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA					
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols)		Auto Ignition Temperature		Flammability Limits in Air by % in Volume:	
NON-FLAMMABLE		N/E		% LEL: N/E % UEL: N/E	
FLASH POINT AND METHOD USED (non-aerosols): N/A		EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.			
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.					
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.					
SECTION 4 - REACTIVITY HAZARD DATA					
STABILITY [X] STABLE [] UNSTABLE		HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR			
Incompatibility (Mat. to avoid): Strong oxidizers.		Conditions to Avoid: Open flame, welding arcs, heat, sparks.			
Hazardous Decomposition Products: Carbon monoxide, carbon dioxide.					
SECTION 5 - HEALTH HAZARD DATA					
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS					
ACUTE EFFECTS:					
Inhalation: Excessive inhalation of vapors can be harmful & may cause headache, dizziness, asphyxia, anesthetic effects & possible unconsciousness.					
Eye Contact: Slight irritation.			Skin Contact: Slight irritation.		
Ingestion: Possible chemical pneumonitis if aspirated into lungs.					
CHRONIC EFFECTS: None known to humans. Note: some animal data indicates some reports of anemia, liver, kidney, lung, blood damage when excessively exposed to 2-butoxyethanol.					
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.					
EMERGENCY FIRST AID PROCEDURES					
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.					
Skin Contact: Wash with soap and water. If irritated, seek medical attention.					
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.					
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.					
SECTION 6 - CONTROL AND PROTECTIVE MEASURES					
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH / MSHA for organic vapors.					
Protective Gloves: Disposable latex gloves suggested.			Eye Protection: Safety glasses recommended.		
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.					
Other Protective Clothing & Equipment: None					
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.					
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE					
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. Dilute with water and flush to sewer.					
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.					
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.					
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.					

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only