



RECTORSEAL

A CSW Industrials Company

SAFETY DATA SHEET

K.O. DIRT BLASTER™

Dirt and grease stripper

SECTION 1 – PRODUCT AND COMPANY INFORMATION

Product Name

K.O. Dirt Blaster™

Product Codes

88438

Chemical Family

Organic

Use

Cleaner and degreaser

Manufacturer's Name

The RectorSeal Corporation
2601 Spenwick Drive
Houston, Texas 77055 USA

Date of Validation

February 19, 2018

Date of Preparation

February 19, 2018

HMIS Codes

Health 2

Flammability 0

Reactivity 0

PPI B

Emergency Telephone No.

Chemtrec 24 Hours

(800)-424-9300 USA

(703)-527-3887 International

Technical Service Telephone No.

(800)-231-3345 or (713)-263-8001

SECTION 2 – HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards

Carcinogen, Target Organ Effect, Harmful by ingestion, Irritant

Target Organs

Liver, pancreas, Blood, Central nervous system, Heart, Kidney

GHS Classification

Acute toxicity, Oral (Category 4)

Skin irritation (Category 2)

Eye irritation (Category 2B)

Carcinogenicity (Category 2)

GHS Label elements, including precautionary statements



GHS04: Compressed Gas Cylinder

GHS07: Exclamation Mark

GHS08: Health Hazard

Signal Word: **Warning**

Hazard statement(s)

H302 - Harmful if swallowed.

H315 + H320 - Causes skin and eye irritation.

H351 - Suspected of causing cancer.

Precautionary statement(s)

P281 - Use personal protective equipment as required.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Summary Of Acute Hazards

Repeated inhalation may cause dizziness, nausea and CNS effects. May cause severe eye and skin irritation.

Route Of Exposure, Signs And Symptoms

INHALATION

Inhalation of high concentrations may cause central nervous system effects characterized by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure.

EYE CONTACT

Contact with eyes may cause severe irritation.

SKIN CONTACT

Irritation and drying.

INGESTION

May cause irritation of the digestive tract. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure.

SUMMARY OF CHRONIC HAZARDS

Skin irritation, contact dermatitis, and defatting.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver, or kidneys may have increased susceptibility to excessive exposure.

K.O. DIRT BLASTER™

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient: Methylene Chloride
Percentage By Weight: ---
CAS Number: 75-09-2
EC#: 200-838-9

SECTION 4 – FIRST AID MEASURES

If inhaled: If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential.

If on skin: Immediately wash with soap and water. Remove and wash any contaminated clothing.

If in eyes: Flush eyes with large amounts of water for 15 minutes. Get medical attention if irritation persists.

If swallowed: If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

SECTION 5 – FIRE FIGHTING MEASURES

Extinguishing Media

Foam, dry chemical, CO₂, or water fog.

Special Fire Fighting Procedures: Wear self-contained full face piece breathing apparatus and full body protective clothing. Hazardous decomposition products possible (see Section 10). Evacuate area. Dike area as run-off may create additional environmental contamination.

Unusual Fire And Explosion Hazards: Aerosol cans are under pressure– exposure to temperatures above 120°F (48°C) can cause bursting or "rocketing" of cans.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Use absorbent materials to prevent footing hazard and to contain. Ventilate area with forced air ventilation. Avoid flushing into sewers, drains, waterways, and soil. Wear protective clothing and respiratory protection during cleanup.

K.O. DIRT BLASTER™

SECTION 7 – HANDLING AND STORAGE

Precautions To Be Taken In Handling And Storing: Shake well before using. Keep away from heat and open flames. Prolonged exposure to direct sunshine or storage above 120°F (48°C) may cause can to burst. Do not puncture or incinerate can.

Other Precautions: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues; treat as if full and observe all products precautions.

KEEP OUT OF REACH OF CHILDREN.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredient	Units
------------	-------

Methylene Chloride

ACGIH TLV:	50 ppm
------------	--------

OSHA PEL:	25 ppm
-----------	--------

OSHA STEL:	125 ppm
------------	---------

Respiratory Protection (Specify Type): In confined, poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air respirators during soldering operations until fumes have dissipated.

Ventilation – Local Exhaust: Acceptable

Special: Explosion proof

Mechanical (General): Acceptable

Other: N/A

Protective Gloves: Wear rubber gloves.

Eye Protection: Safety glasses (ANSI Z-87.1 or equivalent)

Other Protective Clothing Or Equipment: Chemical resistant coveralls recommended.

Work/Hygienic Practices: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Boiling point:	104°F (40°C) @ 760mm Hg
----------------	-------------------------

Specific gravity (H ₂ O = 1):	1.27
--	------

Vapor pressure (mmHg):	350 mm Hg @ 68°F (20°C)
------------------------	-------------------------

Melting point:	N/A
----------------	-----

Vapor Density (Air = 1):	2.9
--------------------------	-----

Evaporation rate (Ethyl Acetate = 1):	> 1
---------------------------------------	-----

Appearance/Odor:	Clear liquid/Citrus odor
------------------	--------------------------

Solubility in water:	Insoluble
----------------------	-----------

Volatile Organic Compounds (VOC) Content (theoretical percentage by weight):	0% or 0 g/L (VOC Exempt)
---	--------------------------

K.O. DIRT BLASTER™

Flash point:	None
Lower explosion limit:	N/D
Upper explosion limit:	N/D
Aerosol flame extension:	Negative

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable

Conditions To Avoid: Do not store in temperatures above 120°F (48°C).

Incompatibility (Materials To Avoid): Oxidizers, acids and bases.

Hazardous Decomposition Products: CO, CO₂, and fragmented hydrocarbons.

Hazardous Polymerization: Will not occur.

SECTION 11 – TOXICOLOGY INFORMATION

Chronic Health Hazards

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

Methylene chloride has been shown to cause cancer in certain laboratory animals. Risk to your health depends on level and duration of exposure.

Carcinogenicity - rat - Inhalation

Tumorigenic:	Carcinogenic by RTECS criteria.
Endocrine:	Tumors.

Limited evidence of carcinogenicity in animal studies

IARC: 2B - Group 2B:	Possibly carcinogenic to humans (Methylene chloride)
NTP:	Reasonably anticipated to be a human carcinogen (Methylene chloride)

Toxicology Data

Ingredient Name

Methylene Chloride

Oral-Rat LD50:	1600 mg/kg
Inhalation-Rat LC50:	88,000 mg/m ³ /30M

SECTION 12 – ECOLOGICAL INFORMATION

Ecological Data

Ingredient Name:	Methylene Chloride
Food Chain Concentration Potential:	None
Waterfowl Toxicity	N/A
BOD	N/A
Aquatic Toxicity	N/A

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Classification: Aerosols

Disposal Method: Empty containers can be disposed of in trash. Full containers should be depressurized to separate liquid phase. The liquid phase is considered a U080 waste and should be incinerated. Dispose of all liquid waste in accordance with all local, state and federal regulations.

SECTION 14 – TRANSPORTATION INFORMATION

DOT: UN1950, Aerosols, Class 2.2, ERG#126
Ocean (IMDG): UN1950, Aerosols, Class 2.2, LTD-QTY, EMS-No: F-A, S-A
Air (IATA): UN1950, Aerosols, Class 2.2, ERG#126
WHMIS (Canada): Class A, (Class D Division 1, Subdivision B)

SECTION 15 – REGULATORY INFORMATION

Regulatory Data

Ingredient Name:	Methylene Chloride
SARA 313	Yes
TSCA Inventory	Yes
CERCLA RQ	1000 lbs.
RCRA Code	U080

California Proposition 65



WARNING: This product can expose you to chemicals including Methylene Chloride, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

SECTION 16 – OTHER INFORMATION

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made.

Consult RectorSeal for further information: (713) 263-8001