## MATERIAL SAFETY DATA SHEET

SATIN GLOW - all bases Page: 1

PRODUCT NAME: SATIN GLOW - all bases HMIS CODES: H F R P

PRODUCT CODE: 4850, 4800, 4810, 4820, 4830 1 0 0 B

UPC #:

======= SECTION I - MANUFACTURER IDENTIFICATION ==========

MANUFACTURER'S NAME: PARKER PAINT

ADDRESS : 3003 SOUTH TACOMA WAY

TACOMA, WA 98409

**EMERGENCY PHONE** : 1-800-255-3924 **DATE PRINTED** : 05/10/05 **INFORMATION PHONE** : 253-473-1122 **NAME OF PREPARER** : J. BURNWORTH

====== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ========

VAPOR PRESSURE WEIGHT

REPORTABLE COMPONENTS CAS NUMBER mm Hg @ TEMP PERCENT

\*\*\* NO REPORTABLE QUANTITIES OF HAZARDOUS INGREDIENTS ARE PRESENT \*\*\*

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

======= SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =======

BOILING RANGE:212 Deg FSPECIFIC GRAVITY (H2O=1):1.35VAPOR DENSITY:LIGHTER THAN AIREVAPORATION RATE:SLOWER THAN ETHER

**SOLUBILITY IN WATER:** DILUTABLE **COATING V.O.C.:** 0.98 lb/gal

APPEARANCE AND ODOR: COLORED LIQUID WITH AN AMMONIACAL ODOR

======= SECTION IV - FIRE AND EXPLOSION HAZARD DATA =========

FLASH POINT: N/A METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

OSHA FLAMMABILITY CLASS:

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL

**SPECIAL FIREFIGHTING PROCEDURES:** FULL PROTECTIVE EQUIPMENT, INCLUDING A SELF-CONTAINED BREATHING APPARATUS IS RECOMMENDED TO PROTECT FIRE FIGHTERS FROM ANY HAZARDOUS COMBUSTION PRODUCTS.

UNUSUAL FIRE AND EXPLOSION HAZARDS: WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD UP AND EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

STABILITY: STABLE

CONDITIONS TO AVOID: DO NOT HEAT ABOVE 200 F.

INCOMPATIBILITY (MATERIALS TO AVOID): NONE KNOWN AT THIS TIME.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: NONE KNOWN AT THIS TIME.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

----- SECTION VI - HEALTH HAZARD DATA -----

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: INHALATION OF HIGH CONCENTRATIONS OF VAPORS MAY CAUSE HEADACHE, NAUSEA AND IRRITATION OF THE NOSE, THROAT, AND LUNGS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: EYE CONTACT MAY CAUSE IRRITATION OR BURNING OF THE EYES. REPEATED LIQUID CONTACT MAY CAUSE SKIN IRRITATION AND DERMATITUS.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: NONE KNOWN AT THIS TIME.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: SWALLOWING CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. VOMITING CAN RESULT IN ASPIRATION OF MATERIAL INTO THE LUNGS WHICH CAN CAUSE CHEMICAL PNEUMONITIS.

HEALTH HAZARDS (ACUTE AND CHRONIC):

ACUTE: (SHORT TERM) OVER EXPOSURE MAY CAUSE HEADACHE, NAUSEA, SKIN AND EYE IRRATATION. CHRONIC: (LONG TERM) UNPROTECTED OVER EXPOSURE TO MISTS FROM SPRAY APPLICATION MAY CAUSE LUNG DISEASE (SILICOSIS).

CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN AT THIS TIME. EMERGENCY AND FIRST AID PROCEDURES:

## MATERIAL SAFETY DATA SHEET

SATIN GLOW - all bases

Page:

INHALATION: REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED, APPLY ARTIFICAL RESPIRATION. CONSULT A PHYSICIAN.

EYE CONTACT: WASH EYES WITH CLEAN WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN.

SKIN CONTACT: WASH AFFECTED AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN.

INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. CONSULT A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

======= SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE ============= STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: VENTILATE AREA. PREVENT SKIN AND EYE CONTACT AND BREATHING OF VAPOR. CONTAIN AND REMOVE WITH INERT ABSORBENT.

WASTE DISPOSAL METHOD: DO NOT ALLOW MATERIAL TO CONTAMINATE GROUND WATER SYSTEMS. ABSORB LARGE SPILLS WITH SAND, CLAY, OR DIATOMACEOUS EARTH. DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL DISPOSAL REQUIREMENTS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: DO NOT STORE ABOVE 200 F.

OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.

RESPIRATORY PROTECTION: NOT REQUIRED FOR BRUSH AND ROLL APPLICATION. FOR SPRAY APPLICATION, WEAR A PROPERLY FITTED NIOSH/MSHA (TC-23C) APPROVED VAPOR/PARTICULATE RESPIRATOR UNTIL ALL VAPORS AND SPRAY MIST ARE EXHAUSTED.

**VENTILATION:** PROVIDE SUFFICIENT VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAMINANT CONCENTRATION BELOW APPLICABLE OSHA PEL OR ACGIH TLV OCCUPATIONAL EXPOSURE LIMITS. (SECTION II)

PROTECTIVE GLOVES: IMPERVIOUS GLOVES ARE RECOMMENDED TO PREVENT SKIN CONTACT.

EYE PROTECTION: USE CHEMICAL SAFETY GOGGLES OR FACE SHIELD TO PREVENT EYE CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: COVERALLS, GLOVES AND HOOD ARE RECOMMENDED DURING SPRAY APPLICATION. PROTECTIVE CREAMS MAY BE USED FOR EASE OF CLEAN-UP, NOT FOR PROTECTION.

WORK/HYGIENIC PRACTICES: WASH HANDS BEFORE EATING OR USING THE RESTROOM.

OR REPRESENTATION WITH RESPECT TO SUCH INFORMATION IS INTENDED OR GIVEN.

AS OF THE DATE OF PREPARATION OF THIS DOCUMENT, THE FOREGOING INFORMATION IS BELIEVED TO BE ACCURATE ND IS PROVIDED IN GOOD FAITH TO COMPLY WITH APPLICABLE FEDERAL AND STATE LAW(S). HOWEVER, NO ARRANTY