


: 140 MATERIAL SAFETY DATA SHEET

NFPA 704

HMS

MANUFACTURER'S NAME: THE W. W. HENRY COMPANY
5608 SOTO STREET
HUNTINGTON PARK, CA 90255
EMERGENCY TELEPHONE: 213/583-4961



DATE OF PREPARATION: REVISED: 5-05-87

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NUMBER: #140 PRODUCT NAME: COVE BASE CEMENT

PRODUCT CLASS: HEAVY BROWN PASTE ADHESIVE

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT:	PERCENT:	OCCUPATIONAL EXPOSURE LIMITS	VAPOR PRESSURE:
ISOPROPYL ALCOHOL (ISOPROPANOL)	10 - 15%	400 PPM TLV	400 PPM
CAS # 67630			32 MM @ 68 DEG.F

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: OSHA: NONE DOT: NONE
FLASH POINT: 71 DEG.F
LEL: 2%

EXTINGUISHING MEDIA: CO2: X DRY CHEMICAL: X WATER FOG: OTHER:
FOAM: X "ALCOHOL" FOAM:

UNUSUAL FIRE AND EXPLOSION HAZARDS: IN FIRE SHOULD BE KEPT COOL TO AVOID BURSTING OF CONTAINERS OR LIDS.

SPECIAL FIREFIGHTING PROCEDURES: NONE KNOWN

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE: IRRITATION OF EYES, NOSE AND THROAT; POSSIBLE MILD NARCOSIS OR INTOXICATION.
SYMPTOMS: RUNNY NOSE, TEARS, AND THROAT DISCOMFORT
CARCINOGENIC STATUS: CONTAINS NO OSHA, NTP OR IARC CARCINOGENS
POTENTIAL HEALTH RISK: MAY CAUSE EYE DISCOMFORT

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: NONE KNOWN FOR ISOPROPANOL
PRIMARY ROUTE(S) OF ENTRY: DERMAL: X INHALATION: X INGESTION:
EMERGENCY AND FIRST AID PROCEDURES: MOVE PERSON TO FRESH AIR; APPLY ARTIFICIAL RESPIRATION IF NECESSARY. GET MEDICAL ATTENTION.

SECTION VI - REACTIVITY DATA

STABILITY: STABLE HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
HAZARDOUS DECOMPOSITION PRODUCTS: SMOKE, OXIDES OF CARBON
CONDITIONS TO AVOID: HEAT AND SOURCES OF IGNITION
INCOMPATIBILITY (MATERIALS TO AVOID): OXIDIZING AGENTS

SECTION III - PHYSICAL DATA

BOILING RANGE: 180-220 DEG.F VAPOR DENSITY: HEAVIER THAN AIR
EVAPORATION RATE: SLOWER THAN ETHER % VOLATILE VOLUME: 35%
WT/GAL: 11.6 LBS. % WATER VOLUME: 5%

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: EXTINGUISH OR REMOVE SOURCES OF IGNITION. SCOOP INTO CONTAINERS AND DRY IN A SAFE PLACE.

WASTE DISPOSAL METHOD: NORMAL SOLID WASTE DISPOSAL

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION: IF VAPORS EXCEED 400PPM, USE AN AIR-SUPPLIED MASK OR NIOSH APPROVED RESPIRATORY DEVICE FOR ORGANIC VAPORS
VENTILATION: TO KEEP VAPORS BELOW 400 PPM

PROTECTIVE GLOVES: ONLY TO PREVENT SOILED AND STICKY HANDS

EYE PROTECTION: HEAVY PASTE, UNLIKELY TO SPLASH. DO NOT SMEAR INTO EYES FROM OTHER PROTECTIVE EQUIPMENT: NONE
HANDS OR TOOLS.
HYGIENIC PRACTICES: WASH SKIN WITH SOAP AND WATER
EYES: FLUSH WITH WATER AND CALL MEDICAL HELP

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: KEEP AWAY FROM HEAT AND SOURCES OF IGNITION.
OTHER PRECAUTIONS: NONE

SECTION X - TRANSPORTATION DATA

D.O.T. - UNREGULATED: X

REGULATED:
SHIPPING NAME:
HAZARD CLASS:
LABEL REQUIRED:

I.M.C.O. - UN(MA) NO: 1133

CLASS: 3.3

PAGE: 3123