

800102-00 MOBILCER A
MATERIAL SAFETY DATA BULLETIN

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: MOBILCER A
SUPPLIER: EXXONMOBIL OIL CORPORATION
3225 GALLOWS RD.
FAIRFAX, VA 22037
24 - Hour Emergency (call collect): 609-737-4411
Product and MSDS Information: 800-662-4525 856-224-4644
CHEMTREC: 800-424-9300 202-483-7616

2. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAMES AND SYNONYMS: PETROLEUM EMULSION
INGREDIENTS CONSIDERED HAZARDOUS TO HEALTH:
Substance Name Wt%

FORMALDEHYDE (50-00-0) <1
See Section 15 for European Label Information.
See Section 8 for exposure limits (if applicable).

3. HAZARDS IDENTIFICATION

US OSHA HAZARD COMMUNICATION STANDARD: This product may be capable of generating 0.1 ppm or greater formaldehyde vapors under certain use conditions. According to OSHA, 29 CFR Part 1910.1048, formaldehyde vapors may be considered hazardous if workplace airborne concentrations exceed 0.1 ppm.
EFFECTS OF OVEREXPOSURE: Exposure to airborne concentrations of formaldehyde in excess of 0.1 ppm may cause discomfort in the stomach and pharynx and irritation of the eyes, nose and throat of some individuals. Sensitization may also occur in some individuals.
EMERGENCY RESPONSE DATA: Milky Buff Emulsion. Wax will burn if water evaporates from emulsion. May generate irritating vapors when burning. DOT ERG No. : NA

4. FIRST AID MEASURES

EYE CONTACT: Flush thoroughly with water. If irritation occurs, call a physician.
SKIN CONTACT: Wash contact areas with soap and water.
INHALATION: Remove from further exposure. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance and call a physician. If breathing has stopped, use mouth to mouth resuscitation.
INGESTION: Not expected to be a problem. However, if greater than 1/2 liter (pint) ingested, immediately give 1 to 2 glasses of water

and call a physician, hospital emergency room or poison control center for assistance. Do not induce vomiting or give anything by mouth to an unconscious person.

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Carbon dioxide, foam, dry chemical and water fog.
SPECIAL FIRE FIGHTING PROCEDURES: This material will not burn; however, use standard chemical fire fighting procedures and consider the hazards of other involved materials. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.
SPECIAL PROTECTIVE EQUIPMENT: For fires in enclosed areas, fire fighters must use self-contained breathing apparatus.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Wax will burn if water evaporates from emulsion. May generate irritating vapors when burning.
Flash Point C(F): NA Flammable limits - LEL: NA, UEL: NA.
NFPA HAZARD ID: Health: 0, Flammability: 0, Reactivity: 0
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide. Paraffin fume.

6. ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES: Report spills as required to appropriate authorities. U. S. Coast Guard regulations require immediate reporting of spills that could reach any waterway including intermittent dry creeks. Report spill to Coast Guard toll free number (800) 424-8802. In case of accident or road spill notify CHEMTREC (800) 424-9300.
PROCEDURES IF MATERIAL IS RELEASED OR SPILLED: Adsorb on fire retardant treated sawdust, diatomaceous earth, etc. Shovel up and dispose of at an appropriate waste disposal facility in accordance with current applicable laws and regulations, and product characteristics at time of disposal.
ENVIRONMENTAL PRECAUTIONS: Prevent spills from entering storm sewers or drains and contact with soil.
PERSONAL PRECAUTIONS: See Section 8

7. HANDLING AND STORAGE

HANDLING: Avoid prolonged repeated skin contact and breathing mists/vapors.
STORAGE: Keep from freezing.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION: Use in well ventilated area.
RESPIRATORY PROTECTION: No special requirements under ordinary conditions of use and with adequate ventilation.
EYE PROTECTION: Normal industrial eye protection practices should be employed.
SKIN PROTECTION: If prolonged or repeated skin contact is likely, impervious gloves should be worn. Good personal hygiene practices should always be followed.

---TWA--- ----STEL--- NOTE
Substance Name (CAS-No.) Source ppm mg/m3 ppm mg/m3

FORMALDEHYDE (50-00-0)

OSHA 0.75 2

SENSITIZER ACGIH 0.3 0.37 CEILING

NOTE: Limits shown for guidance only. Follow applicable regulations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Typical physical properties are given below. Consult Product Data Sheet for specific details.

APPEARANCE: Emulsion

COLOR: Milky Buff

ODOR: Bland

ODOR THRESHOLD-ppm: NE

pH: 7.1

BOILING POINT C(F): > 100(212)

MELTING POINT C(F): NA

FLASH POINT C(F): NA

FLAMMABILITY: NE

AUTO FLAMMABILITY: NA

EXPLOSIVE PROPERTIES: NA

OXIDIZING PROPERTIES: NA

VAPOR PRESSURE-mmHg 20 C: 17.5

VAPOR DENSITY: > 2.0

EVAPORATION RATE: NE

RELATIVE DENSITY, 15/4 C: 1

SOLUBILITY IN WATER: Emulsifies

PARTITION COEFFICIENT: > 3.5

VISCOSITY AT 40 C, cSt: NA

VISCOSITY AT 100 C, cSt: NA

POUR POINT C(F): NA

FREEZING POINT C(F): NE

VOLATILE ORGANIC COMPOUND: NE

NA=NOT APPLICABLE NE=NOT ESTABLISHED D=DECOMPOSES

FOR FURTHER TECHNICAL INFORMATION, CONTACT YOUR MARKETING REPRESENTATIVE

10. STABILITY AND REACTIVITY

STABILITY (THERMAL, LIGHT, ETC.): Stable.

CONDITIONS TO AVOID: Heat. Heat produces dehydration. Freezing temperatures.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide. Paraffin fume.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL DATA

---ACUTE TOXICOLOGY---

ORAL TOXICITY (RATS): Practically non-toxic (LD50: greater than 2000 mg/kg). ---Based on testing of similar products and/or the components.

DERMAL TOXICITY (RABBITS): Practically non-toxic (LD50: greater than 2000 mg/kg). ---Based on testing of similar products and/or the components.

INHALATION TOXICITY (RATS): Not established

EYE IRRITATION (RABBITS): Practically non-irritating. (Draize score: greater than 6 but 15 or less). ---Based on testing of similar products and/or the components.

SKIN IRRITATION (RABBITS): Practically non-irritating. (Primary Irritation Index: greater than 0.5 but less than 3). ---Based on testing of similar products and/or the components.

---CHRONIC TOXICOLOGY (SUMMARY)---

****This product contains formaldehyde which has caused nasal cancer at 15 ppm in rats. NIOSH recommends formaldehyde be handled as a suspected human carcinogen.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE AND EFFECTS: Not established.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: The product is suitable for processing by an approved recycling facility or can be disposed of at any government approved waste disposal facility. Use of these methods is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.

RCRA INFORMATION: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity, or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

14. TRANSPORT INFORMATION

USA DOT: NOT REGULATED BY USA DOT.
RID/ADR: NOT REGULATED BY RID/ADR.
IMO: NOT REGULATED BY IMO.
IATA: NOT REGULATED BY IATA.

15. REGULATORY INFORMATION

Governmental Inventory Status: All components comply with TSCA.

EU Labeling: EU labeling not required.

U.S. Superfund Amendments and Reauthorization Act (SARA) Title III:

This product contains no "EXTREMELY HAZARDOUS SUBSTANCES".

SARA (311/312) REPORTABLE HAZARD CATEGORIES:

CHRONIC

This product contains no chemicals subject to the supplier notification requirements of SARA (313) toxic release program.

The following product ingredients are cited on the lists below:

CHEMICAL NAME	CAS NUMBER	LIST CITATIONS
PARAFFIN WAX FUME		1, 10, 19, 20, 23
FORMALDEHYDE (0.07%)	50-00-0	1, 3, 5, 7, 9, 22,

25

--- REGULATORY LISTS SEARCHED ---

- | | | | | |
|-------------|-----------|-------------|-----------------|-----------|
| 1=ACGIH ALL | 6=IARC 1 | 11=TSCA 4 | 16=CA P65 CARC | 21=LA RTK |
| 2=ACGIH A1 | 7=IARC 2A | 12=TSCA 5a2 | 17=CA P65 REPRO | 22=MI 293 |
| 3=ACGIH A2 | 8=IARC 2B | 13=TSCA 5e | 18=CA RTK | 23=MN RTK |

4=NTP CARC 9=OSHA CARC 14=TSCA 6 19=FL RTK 24=NJ RTK
5=NTP SUS 10=OSHA Z 15=TSCA 12b 20=IL RTK 25=PA RTK
26=RI RTK

Code key: CARC=Carcinogen; SUS=Suspected Carcinogen; REPRO=Reproductive

16. OTHER INFORMATION

Precautionary Label Text:

CONTAINS FORMALDEHYDE

CAUTION!

PRODUCT MAY BE CAPABLE OF GENERATING > 0.1 PPM FORMALDEHYDE VAPORS UNDER CERTAIN USE CONDITIONS.

POTENTIAL CANCER HAZARD.

Avoid breathing mist or vapor. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling.

FIRST AID: If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Call a physician immediately.

For industrial use only. Not intended or suitable for use in or around a household or dwelling.

Empty container may contain product residue, including flammable or explosive vapors. Do not cut, puncture, or weld on or near container.

All label warnings and precautions must be observed until container has been thoroughly cleaned or destroyed.

Refer to product Material Safety Data Bulletin for further safety and health information.

USE: WAX EMULSION

NOTE: PRODUCTS OF EXXON MOBIL CORPORATION AND ITS AFFILIATED COMPANIES ARE NOT FORMULATED TO CONTAIN PCBS.

Please call the Customer Response Center on 800-662-4525 for formulation disclosure.

For Internal Use Only: MHC: 1* 1* NE 1* 1*, MPPEC: A, TRN: 800102-00, ELIS: 400320, CMCS97: 970616, REQ: US - MARKETING, SAFE USE: L
EHS Approval Date: 22JUN1999

Legally required information is given in accordance with applicable Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE IN RESPECT TO THE USE OR SUITABILITY OF THE PRODUCT. Nothing is intended as a recommendation for uses which infringe valid patents or as extending any license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users. Use or re-transmission of the information contained herein in any other format than the format as presented is strictly prohibited. Mobil neither represents nor warrants that the format, content or product formulas contained in this document comply with the laws of any other country except the United States of America.

Copyright 1996 Mobil Corporation, All rights reserved

