



MATERIAL SAFETY DATA SHEET

SECTION I

PRODUCT NAME OR NUMBER (as it appears on label): SeBreeze® Country Linen 9000 Fragrance Aerosol Canister-5159	EMERGENCY TELEPHONE NO.: 1-800-535-5053 INFOTRAC
MANUFACTURER'S NAME: Rubbermaid Commercial Products Inc.	DATE OF LAST REVISION : 03/17/04
ADDRESS (Number, Street, City, State and Zip Code): 3124 Valley Avenue, Winchester, VA 22601	MANUFACTURER'S D-U-N-S NO.: NA
HAZARDOUS MATERIAL DESCRIPTION (49 CFR 172.101) Consumer Commodity, ORM-D	
ADDITIONAL HAZARD CLASSES (as applicable): NFPA Rating System: Fire-3/Health-1/Reactivity-0	
CHEMICAL FAMILY: Aerosol Mixture	FORMULA: NA

SECTION II - INGREDIENTS (list all ingredients) 100% Needed

CAS REGISTRY NO.	%V	CHEMICAL NAME(S)	Listed as a Carcinogen in NTP, IARC or OSHA 1910(z) (specify)
Fragrance Mixture*	12-16	Proprietary	NE
75-37-6	45-55	Dymel 152A	NE
67-64-1	25-35	2-Propanone *	** 750ppm (1780 mg/m ³)TLV; 1000 ppm (2380 mg/m ³) STEL (ACGIH); 750 ppm (1800 mg/m ³) PEL; 1000 ppm (2400 mg/m ³) STEL (OSHA); 250 ppm (590 mg/m ³) TWA (NIOSH)
111-90-0	5-10	Ethoxydiglycol *	NE
NE	<1	Odor Neutralizer	NE

*This product contains the following toxic chemicals subject to reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act and 40 CFR 372:

- Glycol Ether (Cas #: NA, Concentration: 8 %)
- Acetone (Cas # 67-64-1, Concentration: 29.5 %)

SECTION III - PHYSICAL DATA

BOILING POINT: ND	SPECIFIC GRAVITY (H ₂ O=1):	0.900-1.00 g/ml		
VAPOR PRESSURE: NA	PERCENT VOLATILE BY VOLUME (%):	NA	PERCENT SOLID BY WEIGHT (%):	0
VAPOR DENSITY (AIR = 1):	NA	EVAPORATION RATE (n-butyl acetate=1):	ND	
SOLUBILITY IN WATER:	Insoluble	pH=:	NA	
APPEARANCE AND ODOR: Clear liquid, pleasantly scented.			IS MATERIAL: LIQUID GAS PASTE GEL	

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	METHOD USED:	FLAMMABLE LIMITS:	LEL	UEL
(deg C): < - 20 C	TCC		ND	ND

EXTINGUISHING MEDIA: **chemical, foam or carbon dioxide.**

SPECIAL FIRE FIGHTING PROCEDURES: **The use of self-contained breathing apparatus and protective clothing is recommended for fire fighters. Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool. Avoid spreading burning liquid with water used to cooling purposes.**

Unusual Fire & Explosion Hazards: Prolonged exposure to temperatures above 130°F may cause cans to burst.

SECTION V-HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE: Eyes Contact: May cause irritation. Skin Contact: May cause irritation. Inhalation: May cause breathing difficulties. Deliberately concentrating and inhaling vapors may be harmful or fatal. Ingestion: Harmful or fatal.	THRESHOLD LIMIT VALUE: Not determined.
--	---

EMERGENCY AND FIRST AID PROCEDURES: **Eye:** Flush with plenty of water for at least 15 minutes. **Skin:** Wash with soap & water. **Contact a physician if irritation persists.** **Inhalation:** Remove victim to fresh air. **Administer oxygen if needed.** **Ingestion:** Do not induce vomiting. **Contact a physician immediately.**

SECTION VI-REACTIVITY DATA

STABILITY:	UNSTABLE		CONDITIONS TO AVOID: Temperatures above 130°F
	STABLE	XXX	
INCOMPATIBILITY (materials to avoid): None known.			
HAZARDOUS DECOMPOSITION PRODUCTS: None known.			
HAZARDOUS	MAY OCCUR		CONDITIONS TO AVOID: None known.
POLYMERIZATION	WILL NOT OCCUR	XXX	

SECTION VII-SPILL OR LEAK PROCEDURES

Leak and Spill Procedure: Pick-up excess with absorbent material and discard in accordance with regulations. Flush surfaces with IPA and rinse with soap & water.

Waste Disposal: Review federal, provincial and local government requirements prior to disposal.

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (specify type): Not normally required.		
VENTILATION	LOCAL EXHAUST (Specify Rate): General room ventilation is normally sufficient.	SPECIAL: None.
	MECHANICAL (General) (Specify Rate): Acceptable.	OTHER: None.
PROTECTIVE GLOVES (specify type): Rubber gloves.		EYE PROTECTION: Recommend safety glasses with side shields.
OTHER PROTECTIVE EQUIPMENT: None required.		

SECTION IX-SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Contents under pressure. Do not store below 32°F or above 130°F. Do not puncture or incinerate containers. Do not use or store near heat, sparks or open flame.

OTHER PRECAUTIONS: Keep this and all chemicals out of the reach of children. Recommended use with ventilation.

This material safety data sheet is intended to meet the specific requirements of 29 CFR 1910.1200 and should be used accordingly. While the information has been obtained from sources believed to be accurate and reliable, no warranty expressed or implied, can be made with regard to its completeness, correctness or accuracy. Any users or handlers of this product who are not under the direct control of Rubbermaid Commercial Products LLC are responsible for evaluating this information in light of their particular situation and are responsible for all losses, damages or expenses that result while this material is under their control. It is also the responsibility of the users and handlers to observe any and all laws and regulations (federal, state and local) concerning the transportation, use, handling, storage and disposal of this product.