

PRODUCT NAME: OVERALL
PRODUCT CODE: 1950, 1900, 1910, 1920, 1930, 1951, 1952, 1960, 1974,
PRODUCT CODE: 1975, 1976, 1977, 1980, 1981, 1984, 1987, 1989, 1991,
EMIS CODES: H F R F
1 0 0 E

SECTION I - MANUFACTURER IDENTIFICATION
MANUFACTURER'S NAME: PARKER PAINT
ADDRESS: PO BOX 11047
TACOMA, WA 98409
DATE PRINTED: 10/29/97
EMERGENCY PHONE: 1-800-255-3924
NAME OF PREPARER: J. BURNWORTH
INFORMATION PHONE: 253-473-1122

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

Table with 4 columns: CAS NUMBER, VAPOR PRESSURE (mm Hg @ TEMP), WEIGHT PERCENT, and HAZARDOUS INGREDIENTS/SARA III INFORMATION.

*** No reportable quantities of hazardous ingredients are present ***

*** No toxic chemical(s) subject to the reporting requirements of section 311 of Title III and of 40 CFR 372 are present. ***
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS
BOILING RANGE: 212 Deg F
SPECIFIC GRAVITY (H2O=1): 1.33
EVAPORATION RATE: SLOWER THAN EITHER COATING VOC; 1.22 lb/gal
SOLUBILITY IN WATER: DIUTABLE
APPEARANCE AND ODOR: COLORED LIQUID WITH AN AMMONIACAL ODOR
SECTION IV - FIRE AND EXPLOSION HAZARD DATA
METHOD USED: N/A
FLASH POINT: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: n/a UPPER: n/a
EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL
SPECIAL FIREFIGHTING PROCEDURES

FULL PROTECTIVE EQUIPMENT, INCLUDING A SELF-CONTAINED BREATHING APPARATUS IS RECOMMENDED TO PROTECT FIRE FIGHTERS FROM ANY HAZARDOUS COMBUSTION PRODUCTS.

UNUSUAL FIRE AND EXPLOSION HAZARDS
WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD UP AND EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

SECTION V - REACTIVITY DATA
STABILITY: STABLE
CONDITIONS TO AVOID: DO NOT HEAT ABOVE 200 F.

INCOMPATIBILITY (MATERIALS TO AVOID): NONE KNOWN AT THIS TIME.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: NONE KNOWN AT THIS TIME.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - HEALTH HAZARD DATA
INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
IRITATION OF HIGH CONCENTRATIONS OF VAPORS MAY CAUSE HEADACHE, NAUSEA AND IRRITATION OF THE NOSE, THROAT, AND LUNGS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE
SKIN CONTACT MAY CAUSE IRRITATION OR BURNING OF THE SKIN. REPEATED LIQUID CONTACT MAY CAUSE SKIN IRRITATION AND DERMATITIS.
SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
NONE KNOWN AT THIS TIME.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
SWALLOWING CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. VOMITING CAN RESULT IN ASPIRATION OF MATERIAL INTO THE LUNGS WHICH CAN CAUSE CHEMICAL PNEUMONITIS.

HEALTH HAZARDS (ACUTE AND CHRONIC)
ACUTE: (SHORT TERM) OVER EXPOSURE MAY CAUSE HEADACHE, NAUSEA, SKIN AND EYE IRRITATION. CHRONIC: (LONG TERM) UNPROTECTED OVER EXPOSURE TO MISTS FROM SPRAY APPLICATION MAY CAUSE LUNG DISEASE (SILICOSIS).
CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN AT THIS TIME.

EMERGENCY AND FIRST AID PROCEDURES
INHALATION: REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED, APPLY ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN. EYE CONTACT: WASH EYES WITH CLEAN WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN. SKIN CONTACT: WASH AFFECTED AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN. INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. CONSULT A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
VENTILATE AREA. PREVENT SKIN AND EYE CONTACT AND BREATHING OF VAPOR. CONTAIN AND REMOVE WITH INERT ABSORBENT. WASTE DISPOSAL METHOD
DO NOT ALLOW MATERIAL TO CONTAMINATE GROUND WATER SYSTEMS. ABSORB LARGER SPILLS WITH SAND, CLAY, OR DIATOMACEOUS EARTH. DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL DISPOSAL REQUIREMENTS.
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: DO NOT STORE ABOVE 200 F.
OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.

SECTION VIII - CONTROL MEASURES
RESPIRATORY PROTECTION
NOT REQUIRED FOR BRUSH AND ROLL APPLICATION. FOR SPRAY APPLICATION, WEAR A PROPERLY FITTED NIOSH/MSHA (TC-11C) APPROVED VAPOR/PARTICULATE RESPIRATOR UNTIL ALL VAPORS AND SPRAY MIST ARE EXHAUSTED.

VENTILATION
PROVIDE SUFFICIENT VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAMINANT CONCENTRATION BELOW APPLICABLE OSHA PEL OR ACGIH TLV OCCUPATIONAL EXPOSURE LIMITS. (SECTION II)

PROTECTIVE GLOVES: IMPERVIOUS GLOVES ARE RECOMMENDED TO PREVENT SKIN CONTACT.
EYE PROTECTION: USE CHEMICAL SAFETY GOGGLES OR FACE SHIELD TO PREVENT EYE CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT
COVERALLS, GLOVES AND HOOD ARE RECOMMENDED DURING SPRAY APPLICATION. PROTECTIVE CREAMS MAY BE USED FOR BASE OF CLEAN-UP, NOT FOR PROTECTION.

WORK/HYGIENIC PRACTICES: WASH HANDS BEFORE EATING OR USING THE RESTROOM.
SECTION IX - DISCLAIMER
AS OF THE DATE OF PREPARATION OF THIS DOCUMENT, THE FORTHGOING INFORMATION IS BELIEVED TO BE ACCURATE AND IS PROVIDED IN GOOD FAITH TO COMPLY WITH APPLICABLE FEDERAL AND STATE LAW(S). HOWEVER, NO WARRANTY OR REPRESENTATION WITH RESPECT TO SUCH INFORMATION IS INTENDED OR GIVEN.